

# ET3000™



- 18 mph (29 km/h)
- 30 mile range
- 3,000 lb. capacity

## TOUGH & DEPENDABLE PRODUCT SOLUTIONS



**This next generation** electric utility vehicle competes with gasoline vehicles in outdoor applications. This vehicle operates at 18 mph and carries loads up to 3,000 lbs. Specifically designed to meet rugged outdoor applications, the ET3000™ is equipped with a 48 volt drive train that travels up to 30 miles in a single charge.

Taylor-Dunn's GT Drive system provides smooth acceleration while carrying heavy cargo during daily applications. ET3000™ standard features include: metal cab and doors, load range E tires, durable frame design, four-wheel hydraulic brakes and heavy duty drive train that ensures reliability and low maintenance costs.

Your actual range will vary depending on how you drive and maintain your vehicle.

<b>SPEED</b>	18 mph	29 km/h
<b>RANGE</b>	30 miles	48 km
<b>LOAD CAPACITY</b>	3,000 lb.	1,363 kg
<b>BED SIZE (WxL)</b>	49.5x78.5 in.	126x199cm
<b>VOLTAGE</b>	48 volt	48 volt
<b>TURNING RADIUS</b>	145 in.	368 cm

**Based on Standard Configuration**

Typical Capacity: Actual load capacity depends on application and vehicle configuration.

### FEATURES & BENEFITS:

- Available with AC drive train
- Zero emissions
- Smooth, quiet operation
- Customizable to fit your application



# ET3000™

## PERFORMANCE

LOAD CAPACITY	3,000 lbs.	1363 kg
MAX SPEED (UNLOADED)	18 mph	29 km/h
TRAVEL DISTANCE	30 miles	48.3 km
TURNING RADIUS	145 inches	368 cm

## DIMENSIONS

OVERALL LENGTH	131 inches	333 cm
OVERALL WIDTH	51 inches	129.5 cm
OVERALL HEIGHT	74 inches	188 cm
WHEEL BASE	51.25 inches	130 cm

## POWER SUPPLY / DRIVE TRAIN

MOTOR	16.3 HP DC Separately Excited
SYSTEM VOLTAGE	48V DC
TRANSMISSION	Oil Bath, Helical Gears. Single Speed
BATTERIES	8 ea. 6V, 250 Amp/h, Lead Acid
CHARGER	48V, Built In Automatic with Interlock, 110 VAC/60Hz

## CHASSIS

FRAME	Unitized Fully Welded, Heavy Duty 14 Gauge Smooth Skin Steel
STEERING	Automotive Type
FRONT SUSPENSION	Leaf Springs w/ Shock Absorbers
REAR SUSPENSION	Leaf Springs w/ Overload Load Coil Springs
DRIVE AXLE	Automotive Type, Differential
BRAKES	4 Wheel, Hydraulic Disc, Hand Operated Parking Brake
SEATS	Split Seat Cushion w/ Full Length Back Rest in Black Vinyl
BUMPERS	Heavy Duty Steel Rear, Shock Absorbing ABS Front

## GENERAL

UNIT WEIGHT	2,475 lbs.	1125 kg
TIRES	Pneumatic 20.5 x 8 x 10 Load Range E	
SEATING CAPACITY	2 Persons	
CONFORMANCE STANDARDS	Type E, ANSI, B56.8, OSHA 1910.178	

## OPTIONS:

- STEEL PANEL BOX
- SPEED OPTION
- CUSTOM MODIFICATIONS
- DOME LIGHT
- PORTABLE CHARGER
- 230V, 50Hz CHARGER
- AC DRIVE TRAIN
- DRIVER / PASSENGER SUN VISORS



Specifications, standard equipment, accessories and modifications are subject to change without notice.  
Your actual range will vary depending on how you drive and maintain your vehicle.



www.taylor-dunn.com  
contact@taylor-dunn.com  
Toll Free (800) 688-8680  
(714) 956-4040 fx: (714) 956-3130